

TA-CA214 / TA-CA238

Camera Support Accessory

Instruction Manual

Thank you for purchasing the TA-CA2(14/38) camera support accessory. TA-CA2(14/38) is designed to be used with handheld and DSLR type cameras. It enables the ability to mount 14.4V ENDURA V-Mount batteries and accessories to simultaneously supply DC power to the camera and camera accessories. In addition, the TA-CA2(14/38) can be adapted to larger camera systems for flexible accessory mounting. Prior to using TA-CA2(14/38), IDX recommends reading this Instruction Manual on how to best use TA-CA2(14/38).

Features


- Various handheld and still cameras can be mounted.
- Compatible with all P-V series plates.
- Regulated DC voltage from optional P-V series plate with ENDURA battery enables longer operation time.
- Ball-joint clamp and cheese plate design enables fully customizable configurations.
- Many mono/tripod adaptors can be mounted.

Specifications

- Dimensions: 15.66 (L) x 3.24 (W) x 0.39 (H) inches *
*Fully extended.
- Weight: 1.25 lbs.
- Material: 6061 aluminum, black anodized.
- Included accessories: 1/4-20" (TA-CA214) or 3/8-16" (TA-CA238) camera mounting screws.

Parts List

Cheese plate "A" with ball-joint clamp



Cheese plate "B"



1/4-20" Screw



3/8-16" Screw



Assembly and Mounting Instructions

1. Cheese plate "A" mounts to the bottom of a handheld type camera with a 1/4-20" or 3/8-16" screw.
2. Attach cheese plate "B" to the ball-joint clamp in any of the cheese plate's 1/4-20" screw holes.

1



2



Assembly and Mounting Instructions (continued)

3. Attach an optional P-V series plate with the appropriate voltage regulation/DC cable.
4. Adjust the plate's position to your liking and tighten the ball-joint clamp by turning the lever.
5. Attach an optional DC-DC cable to the P-V series plate and camera.

*please call or visit our website to check which P-V series plate and DC-DC cable is compatible with your camera.

3



4



5



Usage Examples



Compact



Chest Support



Under Support

General Notes & Safety

- TA-CA2(14/38) will not mount underneath all handheld cameras. The camera's 1/4-20" or 3/8-16" screw hole must be less than 4.5" or 3.7", respectively, from the rear of the camera.
- Do not attempt to modify this unit. All work should be carried out by IDX authorized service personnel only.
- Tighten all levers and screws prior to use to avoid injury and equipment damage.
- If you need any inspection or repairs, please contact your local IDX dealer or IDX office.



IDX System Technology, Inc.
19001 Harbortgate Way, Suite 105 Torrance, CA 90501
Tel: +1-310-328-2850
Fax: +1-310-328-8202
Email: idx.usa@idx.tv